



colortools™

Water Base Wiping Stain

Product Code: **230550**

ColorTools™ Water Base Wiping Stain is a clear tintable stain base that may also be used as is to enhance the color of natural wood. Read Material Safety Data Sheet and label before using.

CHARACTERISTICS:

Coverage:	375 sq. ft. per gallon depending on application method and absorpency of substrate.
Dry Time:	Times may vary due to environmental controls, humidity and application method. Drying time @ 65-70° F.
Open Time:	5 minutes
Dry to Seal:	minimum 2 - 3 hours
Storage:	Keep container closed when not in use. Store in the original container. Do not store above 100°F (37.8°C).
Shelf Life:	12 months from date of manufacture.
VOC:	7.3 g/l (0.06 lb/gal)*
HAPs:	0 lb. VHAP/lb. Solids*

* VOC and HAP content will vary with strength.

TINTING:

Maximum color load is 16 fluid ounces per gallon. Tint with ColorTools™ Water Base Colorants and ColorTools™ Water Base Dye Concentrates.

SURFACE PREPARATION:

Sand wood surface with 150 grit sandpaper until you achieve a white powder. Remove sanding dust from surface. Surface should be free of dirt, grease, oils, wax and sanding dust.

DIRECTIONS FOR USE:

Stir well before using. Pigments will settle over time. This product must be slowly and constantly agitated during application to ensure proper mixing. Read material safety data sheet and all directions prior to use. Test suitability and performance on each substrate prior to use. Apply Rudd ColorTools Water Base stain by spray application. (ColorTools Water Base Spray Stain may be wiped on, but may result in color variation.) Thoroughly wipe off excess material.

Failure to wipe thoroughly may result in loss of adhesion on finish coats. Top-coat with Rudd NuWave Sealer or Rudd NuWave topcoats.

Application Equipment: Product can be applied with most corrosion resistant spray application equipment: conventional air-spray, airless, air-assisted airless, or H.V.L.P. spray equipment. For specific recommendations, contact your sales representative.

Thinning: Thinning is not required. If necessary, thin with ColorTools Water Base Wiping Clear Base. Thinning will result in color variation.

Clean-Up: Use soap and water for wet product. For dried film clean-up use Rudd Premium Lacquer Thinner.

(Avoid breathing vapors, use a NIOSH approved cartridge respirator. Use filters to avoid breathing spray particles or sanding dust.)

FEATURES:

- Excellent clarity and depth of color
- Beautiful grain definition
- Consistent color
- Good workability - long "open time"
- No lap marks
- Easy repairs
- Low VOC
- No HAPs
- Meets LEED 2009 specifications
- Meets NESHAP for wood furniture & building materials
- Reduce emissions, reduce waste disposal

APPLICATION PRECAUTIONS

- ColorTools Water Base Wiping Stains must be wiped off. Failure to wipe off excess material may result in loss of adhesion of clear sealers or topcoats.
- Spraying heavily pigmented stains on maple or other very hard, non-porous woods, may result in loss of adhesion of clear sealers and topcoats. Always remove excess stain to maximize adhesion of clear finishes.
- Maximum color load 16 fluid ounces per gallon.
- ColorTools Water Base Wiping Stains must be top coated.
- ColorTools Water Base Wiping Stains are for use with NuWave Waterborne Sealer or topcoat only.
- If a solvent sealer is desired, please use Rudd Prism Waterborne Wiping Stains.

NOTE: The stain has been tested on a limited number of substrates and under a limited number of topcoats. The user is responsible for testing suitability and performance for their specific application.

SHIPPING/STORAGE INFORMATION:

OSHA Flammability Class: Not Applicable
DOT Class: Not Regulated



1141 NW 50th St, Seattle, WA 98107
Tel: (800) 444-7833
ruddcompany.com

