



color tools™

Solvent Base Wiping Glaze

Product Code: 300637

ColorTools™ Solvent Base Wiping Glaze is a tintable glaze for use on high quality kitchen cabinets, interior doors & millwork and other wood product. Read Material Safety Data Sheet and label before using.

CHARACTERISTICS:

Coverage:	300 - 500 sq. ft. per gallon depending on application method and absorbency of substrate.
Dry Time:	Times may vary due to environmental controls, humidity and application method. Drying time @ 65-70° F.
Dry to handle:	10 minutes
Dry to Seal:	Minimum 60 minutes
Storage:	Keep container closed when not in use. Store in the original container. Do not store above 100°F (37.8°C).
Shelf Life:	12 months from date of manufacture.
VOC:	661 - 697 g/l (5.51 - 5.82 lb/gal)*
HAPs:	0.10 - 0.16 lb. VHAP/lb. Solids*
* VOC and HAP content will vary with tint strength.	

TINTING:

Maximum color load is 8 fluid ounces per gallon. Tint with 844 Colorants.

SURFACE PREPARATION:

Sand wood surface with 150 grit aluminum oxide sandpaper until you achieve a white powder. Remove sanding dust from surface. Surface should be free of dirt, grease, oils, wax and sanding dust.

DIRECTIONS FOR USE:

- Stain the piece, if desired, and allow recommended dry time for stain type.
- Apply seal coat and allow to dry thoroughly. Note: Seal coat must seal off the open grain of the wood or the glaze will penetrate the substrate and will not be able to be removed. When using a lower solids lacquer, use the first finish coat to seal the open grain prior to glazing.
- Sand the seal coat (or first finish coat) with 180 or finer silicon carbide sandpaper.
- Apply Glaze at full strength to select areas or entire door, as desired. Allow to set up briefly, approximately 2-5 minutes. Use a clean damp cloth to carefully remove the glaze from high and open areas.

Dry Times: Thin applications on flat surfaces and simple relief—approximately 3 hours before coating. Thick applications such as crevasses, beading, routing or other deep recesses, require an overnight dry before finishing.

Application Equipment: Product can be applied with most spray application equipment: conventional air-spray, airless, air-assisted airless, or H.V.L.P. spray equipment. A brush or rag can be used for small area.

Thinning: Thinning is not required. If necessary, thin with a small amount of Mineral Spirits. Thinning may result in color variation.

Clean-Up: Clean equipment immediately with Mineral Spirits or Lacquer Thinner.

(Avoid breathing vapors, use a NIOSH approved cartridge respirator. Use filters to avoid breathing spray particles or sanding dust.)

FEATURES:

- Excellent clarity and depth of color
- Beautiful grain definition
- Good workability - long "open time"
- Easy wipe
- Seal in 1 hour
- ColorTools Program includes 39 pre-formulated colors
- Meets NESHAP for wood furniture

APPLICATION PRECAUTIONS

- ColorTools Wiping Stains must be wiped off. Failure to wipe off excess material may result in loss of adhesion of clear sealers or topcoats.
- Spraying heavily pigmented stain on maple or other very hard, non-porous woods, may result in loss of adhesion of clear sealers and topcoats. Always remove excess stain to maximize adhesion of finishes.
- Use ColorTools Base Toner as a two-step system to achieve very dark colors.
- ColorTools Wiping Stains must be top coated
- Maximum color load for ColorTools Wiping Stains Clear Base is 16 fluid ounces.

NOTE: The stain has been tested on a limited number of substrates and under a limited number of topcoats. The user is responsible for testing suitability and performance for their specific application.

SHIPPING/STORAGE INFORMATION:

Flash Point*: 90 - 108° F. Pinsky-Marten
OSHA Flammability Class: Flammable Liquid - Class IC
DOT Class: UN 1263, Paint, 3, PG II

* Variations depend on color.

DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH STAIN MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN SEALED WATER-FILLED METAL CONTAINER. DISPOSE OF ACCORDING TO FEDERAL, STATE OR LOCAL REGULATIONS.



1141 NW 50th St, Seattle, WA 98107
Tel: (800) 444-7833
ruddcompany.com

© Rudd Company, Inc. 04.16

