



color^{tools}TM

Oil Base Glaze - Neutral

Product Code: **300637**

Colortools™ Oil Base Glaze is a neutral tintable wiping glaze for achieving specialty finishes on high quality kitchen cabinets, interior doors & millwork and other wood products.

CHARACTERISTICS:

Coverage:	300 - 500 sq. ft. per gallon depending on application method and absorbency of substrate.
Dry Time:	Times may vary due to environmental controls, humidity and application method.
Dry to handle:	10 minutes @ 65-70° F.
Dry to Seal:	See Directions for Use (below)
Storage:	Keep container closed when not in use. Store in the original container. Do not store above 100°F (37.8°C).
Shelf Life:	12 months from date of manufacture.
VOC:	661- 697 g/l (5.51 - 5.82 lb/gal)*
HAP:	Pounds HAP per Pound Solids 0.10-0.16*

* VOC and HAP content will vary with color and tint strength.

TINTING:

Maximum color load is 8 fluid ounces per gallon of glaze. Tint with Colortools Solvent Base Colorants or 844 Colorants.

SURFACE PREPARATION:

Sand wood surface with 150 grit aluminum oxide sandpaper until you achieve a white powder. Remove sanding dust from surface. Surface should be free of dirt, grease, oils, wax and sanding dust.

DIRECTIONS FOR USE:

- Stain the piece, if desired, and allow recommended dry time for stain type.
- Apply seal coat and allow to dry thoroughly. Note: Seal coat must seal off the open grain of the wood or the glaze will penetrate the substrate and be unable to remove. When using a lower solids clear lacquer as the finish, the first finish coat may be used to seal the open grain prior to glazing.
- Sand the seal coat (or first finish coat) with 180 or finer silicon carbide sandpaper.
- Apply Glaze at full strength to select areas or entire door, depending upon desired effect. Allow to set up briefly, approximately 2-5 minutes. Use a clean damp cloth to carefully remove the glaze from high and open areas.

This product must be top-coated.

Dry Times: Thin applications on flat surfaces and simple relief—allow approximately 3 hours before coating. **Thick applications** such as crevasses, beading, routing or other deep recesses, **require an overnight dry before finishing.**

Application Equipment: Product can be applied with most spray application equipment: conventional air-spray, airless, air-assisted airless, or H.V.L.P. spray equipment. A brush or rag can be used for small areas.

Thinning: Thinning is not required, however, if desired, thin with a small amount of Mineral Spirits. Thinning may result in color variation.

Clean-Up: Clean equipment immediately with Mineral Spirits or Lacquer

FEATURES:

- Great 'open time'
- Excellent workability
- Easy to wipe
- Achieve a variety of decorative effects with different application techniques
- Produce subtle highlights or dramatic color combinations
- Use with stained or solid color backgrounds
- Tint base provides limitless color options

APPLICATION PRECAUTIONS

- Colortools Oil Base Glaze must be thoroughly dry to avoid loss of adhesion over, under and between clear sealers or topcoats.
- Always remove excess glaze to maximize adhesion of finishes.
- Glazes are decorative finishes and may not be suitable for use in some high wear areas. This product has been tested with a limited number of substrates, seal coats and topcoats. The user is responsible for testing suitability and performance for their specific application.

Avoid breathing vapors, use a NIOSH approved cartridge respirator. Use filters to avoid breathing spray particles or sanding dust. Read label and Safety Data Sheet before using.

DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH STAIN OR GLAZE MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE, PLACE RAGS, STEEL WOOL OR WASTE IN SEALED WATER-FILLED METAL CONTAINER. DISPOSE OF ACCORDING TO FEDERAL, STATE OR LOCAL REGULATIONS.

SHIPPING/STORAGE INFORMATION:

Flash Point*: < 73° F. Pinsky-Marten
OSHA Flammability Class: Flammable Liquid - Class IB
DOT Class: UN 1263, Paint, 3, PG II

* Variations depend on color.



1141 NW 50th St, Seattle, WA 98107
Tel: (800) 444-7833
ruddcompany.com

© Rudd Company, Inc. 06.2020

