

CONVERSION VARNISH

MiraVar™ 550

OPAQUE CONVERSION VARNISH—TINT BASE

Product Code: **310695**

MiraVar™ 550 Opaque Conversion Varnish Tint Base is a colorless, two-part conversion varnish for tinting dark custom colors for interior wood cabinetry where a flawless finish is required.

Ideal For

- Kitchen cabinets
- Bathroom cabinets
- Wood placed in high moisture areas
- Residential table and bar tops
- Exceeds KCMA performance tests
- AIM compliant 550 g/l VOC
- NESHAP compliant—JJ (furniture)
- NESHAP compliant—QQQQ (doors & windows)

Benefits

- Achieve dark custom colors
- Exceptional abrasion resistance
- Excellent water and chemical resistance
- Ready to spray after catalyzation
- 24 hour pot life
- Excellent flow and leveling
- High solids—superior build
- Excellent sanding properties
- May be used as a self-seal system
- Super-Low HAP

APPLICATION DATA

SURFACE PREPARATION: “White sand” wood with maximum 150 grit aluminum oxide sandpaper. Remove all sanding dust. Keep free of dirt, grease, silicone oils, lubricants and other contaminants.

APPLICATION EQUIPMENT: This product is designed for spray application through all types of equipment. Mixing or pumping equipment that is in constant contact with Conversion Varnish should be constructed of stainless steel or other anti-corrosive material. Recommended settings below are with trigger pulled.

Airless	No thinning required. Spray at 1000 or 1200 psi 411 or 513 tip
Air Assist	No thinning required. Spray at 700 to 900 psi fluid pressure 10-12 psi air cap 411 or 513 tip
HVLP	No thinning required. Spray at 28 psi through a 1.4 fluid nozzle

THINNING: This product is designed to spray at package viscosity with most application equipment. Thinning requirements may vary with changes in temperature and spray room conditions. If thinning is desired, use 650870 Lacquer Thinner, 652081 VOC Exempt Lacquer Thinner, 652210 No-HAP Lacquer Thinner, or Acetone.

Note: Thinning will reduce film build and may increase VOCs or HAPs, unless using VOC exempt or HAP-free solvents.

AGITATION: This product must be kept under slow, constant agitation, to ensure proper mixing.

CLEAN UP: Use lacquer thinner compliant with local air quality rules and regulations.

FINISHING SYSTEM

MIXING DIRECTIONS: Add 3% (4 fluid ounces) of Rudd 03-143 Catalyst per gallon. Stir well during and after adding catalyst.

POT LIFE: 1 day (24 hours) @ 65-70°F.

STAIN: When staining wood, use Rudd Colortools™ Dye Stain, Colortools™ Spray Only Stain, or Colortools™ Wiping Stain.

SEAL: Apply one coat (3-5 mils wet) of MiraVar 550 tinted to the desired color as its own sealer or one coat (3-4 mils wet) of 310704 MiraVar 550 White, or tinted, Sanding Sealer. Allow to dry 30 minutes*. Sand with 220/320 grit silicon carbide sandpaper before finishing.

FINISH: Apply one or two coats (3-5 mils wet) of MiraVar 550. Allow to dry 40 minutes between coats. Sand between all coats with 220/320 grit silicon carbide sandpaper.

If desired, additional coats may be applied up to a total dry film of 5.0 dry mils.

*Dry times may vary with film thickness, temperature, humidity and air movement.

SAFETY PRECAUTIONS

Avoid breathing vapors, use a NIOSH approved cartridge respirator. Use pre-filters to avoid breathing spray particles or sanding dust.

Flammable Liquid and Vapor: Keep away from heat, sparks and flame. Ensure adequate ventilation during use. Clean up spills with non-sparking tools and inert absorbent material. Store solvent and lacquer soaked rags and filters in water-filled, closed container prior to disposal. Dispose of in safe, approved manner.

Read Material Safety Data Sheet and label before using.

FINISH PERFORMANCE TESTING

KCMA

Vinegar	No Visual Effect
Lemon Juice	No Visual Effect
Orange Juice	No Visual Effect
Grape Juice	No Visual Effect
Catsup	No Visual Effect
Olive Oil	No Visual Effect
100 Proof Alcohol	No Visual Effect
Hot Coffee	No Visual Effect
Edge Soak	Passed 24 hr KCMA test with no softening, discoloration or film defects
Cold Check	Passed 20 cycles @ 5 mils dry film
OTHER	
Hot Water Ring*	No marking at 190° F after 1 hour
Mar Resistance*	Excellent
Adhesion*	Excellent

* Test results may vary with amount of colorant used to achieve desired color.

*** Contact your Sales Representative for available stock sheens and package sizes.***

SPECIFICATIONS

Coverage	441 square feet per gallon @ 1 mil dry film
Viscosity	20-25 Seconds (#2 Zahn @ 75°F)
Sag Resistance	5 mils vertical @ 65-70°F
Solids*	34.7-37.4% by weight 2.68-2.96 lbs per gallon
VOC* (Volatile Organic Compounds)	Calculated: 536-549 g/l (4.5-4.6 lb/gal) Catalyzed: 539-549 g/l (4.49-4.58 lb/gal)
HAP* (Hazardous Air Pollutants)	Pounds per Gallon: 0.037—0.038 Pounds HAP per Pound Solids: < 0.8 (actual 0.0132—0.0140) Pounds HAP per Volume Solids: < 0.48 (actual 0.1327—0.1386)
Dry to Sand	40 minutes @ 65-70°F
Block Free	24 hours @ 5 mils wet
*Variations depend on gloss. CAUTION: Thinning will reduce film build and may increase VOCs and HAPs unless using VOC Exempt or HAP-free thinner.	

APPLICATION PRECAUTIONS

- MiraVar 550 Opaque Conversion Varnish tinted to the desired color may be used as a self seal system.
- Do not use alkaline based products to clean surfaces finished with MiraVar 550 Opaque Conversion Varnish.
- This product MUST be sanded between all coats to ensure proper adhesion.
- This product MUST be re-coated within 8 hours of being sanded.
- Tint only with Colortools™ or 844 Colorants. Do not exceed 8 fl. oz. of colorant per gallon of coating.
- This product is not recommend for exterior use.
- Finish, substrate and curing temperatures should remain above 60°F, extremes of temperature and humidity may affect product performance.
- Total film build of system must not exceed 5.0 dry mils.
- This product has been tested on a limited number of substrates and over a limited number of coatings. The user is responsible for testing suitability and performance for their specific application.
- For best results, use within 12 months of manufactured date.

Shipping & Storage Information

Flash Point: -4°F Pensky-Martin

OSHA Flammability Class: Flammable Liquid—Class IB

DOT Class: Paint, 3, UN 1263, PG II



RUDD COMPANY, INC

Manufacturers of Quality Coatings Since 1912

Rudd Company, Inc., 1141 NW 50th St, Seattle, WA 98107

ruddcompany.com · 206-789-1000

To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance and are subject to change without prior notice. User must contact Rudd Company, Inc. to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. We guarantee our products to conform to Rudd Company, Inc. quality control. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESSED OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.